



PermaDrain® Locking Dome Strainer Kits meet or exceed UPC 810.4–Strainers, and IPC 802.3–Waste Receptors as referenced below:

Waste receptors shall be of an approved type. A removable strainer or basket shall cover the waste outlet of waste receptors

Description

PermaDrain Locking Dome Strainer Kits are designed to prevent debris from entering the drain openings of indirect waste receptors. They are designed for use in new construction and retro-fit applications for drains in existing buildings.

Construction

1–6.2 x 152mm type 316 stainless steel screw for superior corrosion resistance.

1–134mm W x 76mm H Dome Strainer made from engineered polymers to provide impact resistance, chemical resistance and heat resistance up to 102 degrees Celsius.

1–Cross–Strainer™ made from engineered polymers to provide impact resistance, chemical resistance and heat resistance up to 102 degrees Celsius.

2–Gaskets made from polyurethane to ensure a proper fit in various applications.

NOMINAL PIPE SIZE	MODEL#	"A"	"B"	"C"-(PVC GASKET)	"C"-(CAST IRON GASKET)
50mm	PD-2005	152.5mm	140mm	49.5mm - 51mm	51mm - 52mm
80mm	PD-3005	152.5mm	140mm	75mm - 76.5mm	76.5mm - 77.5mm
100mm	PD-4005	152.5mm	140mm	100mm - 101.5mm	101.5mm - 103mm